

data sheet

WK-EOS

CONTROL MODULE FOR RAKO WIRED SYSTEMS



WHAT IS IT?

A hard wired 6 button push button control module.

Customisable and programmable using Rasoft Pro Software.

Rako EOS screwless plate kits are available in the following selection of finishes:

Matt White (WH)

Matt Black (MB)

Satin Chrome (SC)

Polished Chrome (PC)

Matt Bronze (BM)

Antique Brass (AB)

Polished Brass (PB)


Electronics and coverplate supplied separately.

EOS coverplate kits use the code: WP-EOS-XX-XX

Shown opposite:

WK-EOS-6 module complete with WP-EOS-60-SC cover plate kit fitted.

WK-EOS wired push button wall plate controller. Customisable and programmable via RASOFT Pro.



The WK-EOS push button wired control module is programmable via Rako's Rasoft Pro software. Each input is fully customisable and can be addressed to separate Rako Rooms or Channels and activate on press or release, giving a 'Press and Hold' function. Each button is complete with a blue LED indicator, additionally, each input can trigger an internal macro function.

Easy connection to the Rakom wired CAT5 network is by a removable 8 way Krone punch down module that can be installed at first fix stage prior to the push button front control module. This protects the control module from being damaged while building works are being finished.

WK-EOS control modules are designed to be flush mounted to a UK back-boxes



data sheet

WK-EOS


CONTROL MODULE FOR RAKO WIRED SYSTEMS




technical data

| ioeiiiieai ae | Technical data | |
|---------------|--|--|
| dimensions | PCB: 50x50x35mm - flush mount only Cover Plate: 88x88x3mm | |
| input supply | 12-18vdc supply from Rakom CAT5 wired network. | |
| fixing | Flush mounting into standard UK single gang back box, minimum 35mm deep. | |
| weight | Electronics 37g Plate & Grid 141g | |
| climate range | Temperature +2C to +40C Humidity +5% to 95% non condensing. | |
| cable type | UTP CAT5e or CAT6 | |
| terminal type | 8 way Krone punch down (screw terminal option available) | |
| standards | Emissions - EN61000-6-3 : 2007 Immunity - EN61000-6-1 : 2007 | |
| communication | Rakom wired network | |
| memory | Flash memory (non volatile) Firmware upgrades via RASOFT | |


mechanical data





Standard button configurations & part numbers

programming software



telephone +44 (0) 1634 226666 www.rakocontrols.com